


Ourhood, pods Technical Data Sheet (TDS)



Product data		Electrical Rating	
External dimensions:	2225 x 2415 x 1525 mm	Voltage:	230 V AC
Internal dimensions:	2010 x 2145 x 1385 mm	Frequency:	50 HZ
Weight:	Approx. 780 kg	Fuse Rating:	10 A
Climate emission:	3170 kg CO2-eq (PEF)		

Quality and certifications

- CE marked according to EU Directive 2014/35/EU (Low Voltage Directive), EN 62368-1 + A11(SERTIKA, EN 17025 tested)
- CE marked according to Directive 2014/30/EU (Electromagnetic compatibility (EMC)) Class I, EN IEC 61000-6-1 and EN IEC 61000-6-3 (LEITC)
- Door with CE marked Simonswerk Tectus heavy-duty hinges EN 1935 (200.000 cycles)
- CE marked tempered and laminated safety glass according to EN 14449+AC
- Air flow at max.33 l/sek, can be added with electronic flow regulation (UAB ENERSA, certified)
- Forest Stewardship Council (FSC) wood (certificate no. FSC-C 104600)
- Furniture elements sitting/table, EN 16139, level 2 and EN 15372, level2 Danish Technology Institute, EN 17025 - accredited test lab)
- EU Ecolabel textiles (Camira, Kvadrat and Gabriel)
- Sound insulation performance class A (30,1 dB) according to ISO 23351-1/ISO 3741 (FORCE tested)